

## SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Product identifier** : GRIP/AL  
**Product name** : GRIP #4 1K UNIVERSAL ADHESION PROMOTER AEROSOL  
**Product type** : Aerosol.  
**Appearance** : Aerosol.  
**Other means of identification** : GRIP/AL  
**Date of issue/ Date of revision** : 13 May 2025  
**Version** : 1.02  
**Date of previous issue** : 13 May 2025

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** : Coating component.  
**Uses advised against** : Not for sale to or use by consumers.

#### 1.3 Details of the supplier of the safety data sheet

U-POL Limited  
Denington Road  
Wellingborough, Northamptonshire, NN8 2QH  
+44 (0) 1933 230310  
technicalsupport@u-pol.com  
**e-mail address of person responsible for this SDS** : sds-competence@axalta.com

##### National contact

U-POL Netherlands  
B.V. Hoorgoordreef 15  
Amsterdam, Netherlands 1101BA  
+31 20 240 2216  
technicalsupport@u-pol.com

#### 1.4 Emergency telephone number

##### National advisory body/Poison Center

**Telephone number** : 010-456 6700 (9:00-17:00);112

##### Supplier

+(44)-870-8200418

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

**Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

Aerosol 1, H222, H229

Skin Irrit. 2, H315

Eye Irrit. 2, H319

Repr. 2, H361d

STOT SE 3, H336

STOT RE 2, H373

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Hazard pictograms** :



**Signal word** : Danger

**Contains** : toluene

**Hazard statements** : H222, H229 - Extremely flammable aerosol. Pressurized container: may burst if heated.  
H315 - Causes skin irritation.  
H319 - Causes serious eye irritation.  
H336 - May cause drowsiness or dizziness.  
H361d - Suspected of damaging the unborn child.  
H373 - May cause damage to organs through prolonged or repeated exposure.  
H412 - Harmful to aquatic life with long lasting effects.

**Precautionary statements**

**Prevention** : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 - Do not spray on an open flame or other ignition source.  
P260 - Do not breathe dust or mist.  
P251 - Do not pierce or burn, even after use.

**Response** : P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**Storage** : P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

**Disposal** : Not applicable.

**Supplemental label elements** : EUH208 - Contains hydrogen tetrakis[2,2-bis[(allyloxy)methyl]butan-1-olato-O1]bis (ditridecyl phosphito -O")titanate(2-). May produce an allergic reaction.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

## SECTION 2: Hazards identification

### 2.3 Other hazards

**Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**Other hazards which do not result in classification** : None known.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures : Mixture

| Product/ingredient name                                                                               | Identifiers                                                                           | %         | Classification                                                                                                                                                                                    | Specific Conc. Limits, M-factors and ATEs                         | Type    |
|-------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------|
| toluene                                                                                               | REACH #:<br>01-2119471310-51<br>EC: 203-625-9<br>CAS: 108-88-3<br>Index: 601-021-00-3 | ≥25 - ≤50 | Flam. Liq. 2, H225<br>Skin Irrit. 2, H315<br>Repr. 2, H361d<br>STOT SE 3, H336<br>STOT RE 2, H373<br>Asp. Tox. 1, H304<br>Aquatic Chronic 3, H412                                                 | -                                                                 | [1] [2] |
| dimethyl ether                                                                                        | REACH #:<br>01-2119472128-37<br>EC: 204-065-8<br>CAS: 115-10-6<br>Index: 603-019-00-8 | ≥25 - ≤50 | Flam. Gas 1A, H220<br>Press. Gas (Comp.), H280                                                                                                                                                    | -                                                                 | [1] [2] |
| acetone                                                                                               | REACH #:<br>01-2119471330-49<br>EC: 200-662-2<br>CAS: 67-64-1                         | ≥10 - <20 | Flam. Liq. 2, H225<br>Eye Irrit. 2, H319<br>STOT SE 3, H336<br>Aquatic Chronic 2, H411<br>EUH066                                                                                                  | -                                                                 | [1] [2] |
| Reaction mass of ethylbenzene and xylene                                                              | REACH #:<br>01-2119539452-40<br>EC: 905-588-0                                         | ≤3        | Flam. Liq. 3, H226<br>Acute Tox. 4, H312<br>Acute Tox. 4, H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>STOT SE 3, H335<br>STOT RE 2, H373<br>Asp. Tox. 1, H304<br>Aquatic Chronic 3, H412 | ATE [Dermal] = 1100 mg/kg<br>ATE [Inhalation (vapours)] = 11 mg/l | [1]     |
| hydrogen tetrakis[2,2-bis[(allyloxy)methyl]butan-1-olato-O1]bis(ditridecyl phosphito -O")titanate(2-) | EC: 264-709-9<br>CAS: 64157-14-8                                                      | ≤0.2      | Skin Irrit. 2, H315<br>Skin Sens. 1, H317<br>Aquatic Chronic 2, H411<br><b>See Section 16 for the full text of the H statements declared above.</b>                                               | -                                                                 | [1]     |

## SECTION 3: Composition/information on ingredients

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

[1] Substance classified with a physical, health or environmental hazard

[2] Substance with a workplace exposure limit

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- |                                   |                                                                                                                                                                                                                                                                                                                |
|-----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>General</b>                    | : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.                                                                                                          |
| <b>Eye contact</b>                | : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.                                                                                                                                                      |
| <b>Inhalation</b>                 | : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.                                                                                                               |
| <b>Skin contact</b>               | : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.                                                                                                                                                           |
| <b>Ingestion</b>                  | : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.                                                                                                                                                                        |
| <b>Protection of first-aiders</b> | : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. |

### 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains hydrogen tetrakis[2,2-bis[(allyloxy)methyl]butan-1-olato-O1]bis(ditridecyl phosphito -O")titanate(2-). May produce an allergic reaction.

### 4.3 Indication of any immediate medical attention and special treatment needed

- |                            |                                                                                                                             |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| <b>Notes to physician</b>  | : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. |
| <b>Specific treatments</b> | : No specific treatment.                                                                                                    |

See toxicological information (Section 11)

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media** : Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray.

**Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

**Hazardous combustion products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

### 5.3 Advice for firefighters

**Special protective actions for fire-fighters** : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

**Special protective equipment for fire-fighters** : Appropriate breathing apparatus may be required.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.

**For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**6.2 Environmental precautions** : Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

**6.3 Methods and materials for containment and cleaning up** : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

**6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

: Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or watercourses.

**Information on fire and explosion protection**

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

#### Notes on joint storage

Keep away from: oxidizing agents, strong alkalis, strong acids.

#### Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

#### Seveso Directive - Reporting thresholds

##### Danger criteria

| Category | Notification and MAPP threshold | Safety report threshold |
|----------|---------------------------------|-------------------------|
| P3a      | 150 tonnes                      | 500 tonnes              |

### 7.3 Specific end use(s)

**Recommendations** : Not available.

**Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

#### Occupational exposure limits

## SECTION 8: Exposure controls/personal protection

| Product/ingredient name | Identifiers                                                                                    | Exposure limit values                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|-------------------------|------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| toluene                 | REACH #:<br>01-2119471310-51<br>EC:<br>203-625-9<br>CAS:<br>108-88-3<br>Index:<br>601-021-00-3 | <b>Work environment authority Regulation 2018:1 (Sweden, 11/2022)</b> Absorbed through skin , Ototoxicant.<br>TWA 8 hours: 50 ppm.<br>TWA 8 hours: 192 mg/m <sup>3</sup> .<br>STEL 15 minutes: 100 ppm.<br>STEL 15 minutes: 384 mg/m <sup>3</sup> .<br><b>EU OEL (Europe, 1/2022)</b> Absorbed through skin.<br>TWA 8 hours: 192 mg/m <sup>3</sup> .<br>TWA 8 hours: 50 ppm.<br>STEL 15 minutes: 384 mg/m <sup>3</sup> .<br>STEL 15 minutes: 100 ppm. |
| dimethyl ether          | REACH #:<br>01-2119472128-37<br>EC:<br>204-065-8<br>CAS:<br>115-10-6<br>Index:<br>603-019-00-8 | <b>Work environment authority Regulation 2018:1 (Sweden, 11/2022)</b><br>TWA 8 hours: 500 ppm.<br>TWA 8 hours: 950 mg/m <sup>3</sup> .<br>STEL 15 minutes: 800 ppm.<br>STEL 15 minutes: 1500 mg/m <sup>3</sup> .<br><b>EU OEL (Europe, 1/2022)</b><br>TWA 8 hours: 1000 ppm.<br>TWA 8 hours: 1920 mg/m <sup>3</sup> .                                                                                                                                 |
| acetone                 | REACH #:<br>01-2119471330-49<br>EC:<br>200-662-2<br>CAS: 67-64-1                               | <b>Work environment authority Regulation 2018:1 (Sweden, 11/2022)</b><br>TWA 8 hours: 250 ppm.<br>TWA 8 hours: 600 mg/m <sup>3</sup> .<br>STEL 15 minutes: 500 ppm.<br>STEL 15 minutes: 1200 mg/m <sup>3</sup> .<br><b>EU OEL (Europe, 1/2022)</b><br>TWA 8 hours: 500 ppm.<br>TWA 8 hours: 1210 mg/m <sup>3</sup> .                                                                                                                                  |

### Biological exposure indices

No exposure indices known.

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following:  
European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### DNELs/DMELs

#### Product/ingredient name

toluene

#### Result

##### **DNEL - Workers - Long term - Inhalation**

50.3 ppm

Effects: Systemic

##### **DNEL - General population - Long term - Oral**

8.13 mg/kg bw/day

Effects: Systemic

SECTION 8: Exposure controls/personal protection

|                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                | <div><div><b>DNEL - General population - Long term - Inhalation</b><br/>56.5 mg/m<sup>3</sup><br/><u>Effects:</u> Local</div><div><b>DNEL - General population - Long term - Inhalation</b><br/>56.5 mg/m<sup>3</sup><br/><u>Effects:</u> Systemic</div><div><b>DNEL - Workers - Long term - Inhalation</b><br/>192 mg/m<sup>3</sup><br/><u>Effects:</u> Local</div><div><b>DNEL - Workers - Long term - Inhalation</b><br/>192 mg/m<sup>3</sup><br/><u>Effects:</u> Systemic</div><div><b>DNEL - General population - Long term - Dermal</b><br/>226 mg/kg bw/day<br/><u>Effects:</u> Systemic</div><div><b>DNEL - General population - Short term - Inhalation</b><br/>226 mg/m<sup>3</sup><br/><u>Effects:</u> Local</div><div><b>DNEL - General population - Short term - Inhalation</b><br/>226 mg/m<sup>3</sup><br/><u>Effects:</u> Systemic</div><div><b>DNEL - Workers - Long term - Dermal</b><br/>384 mg/kg bw/day<br/><u>Effects:</u> Systemic</div><div><b>DNEL - Workers - Short term - Inhalation</b><br/>384 mg/m<sup>3</sup><br/><u>Effects:</u> Local</div><div><b>DNEL - Workers - Short term - Inhalation</b><br/>384 mg/m<sup>3</sup><br/><u>Effects:</u> Systemic</div></div> |
| dimethyl ether | <div><div><b>DNEL - General population - Long term - Inhalation</b><br/>471 mg/m<sup>3</sup><br/><u>Effects:</u> Systemic</div><div><b>DNEL - Workers - Long term - Inhalation</b><br/>1894 mg/m<sup>3</sup><br/><u>Effects:</u> Systemic</div></div>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| acetone        | <div><div><b>DNEL - Workers - Long term - Inhalation</b><br/>500 ppm<br/><u>Effects:</u> Systemic</div><div><b>DNEL - Workers - Long term - Dermal</b><br/>186 mg/kg bw/day<br/><u>Effects:</u> Systemic</div><div><b>DNEL - Workers - Long term - Inhalation</b></div></div>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |



SECTION 8: Exposure controls/personal protection

|                                          |                                                                                     |
|------------------------------------------|-------------------------------------------------------------------------------------|
|                                          | 1210 mg/m³<br>Effects: Systemic                                                     |
|                                          | <b>DNEL - Workers - Short term - Inhalation</b><br>2420 mg/m³<br>Effects: Local     |
| Reaction mass of ethylbenzene and xylene | <b>DNEL - Workers - Long term - Dermal</b><br>212 mg/kg bw/day<br>Effects: Systemic |
|                                          | <b>DNEL - Workers - Long term - Inhalation</b><br>221 mg/m³<br>Effects: Systemic    |
| <b>PNECs</b>                             |                                                                                     |
| <b>Product/ingredient name</b>           | <b>Result</b>                                                                       |
| toluene                                  | <b>Fresh water</b><br>0.68 mg/l                                                     |
|                                          | <b>Fresh water sediment</b><br>16.39 mg/l                                           |
|                                          | <b>Marine water sediment</b><br>16.39 mg/kg                                         |
|                                          | <b>Sewage Treatment Plant</b><br>13.61 mg/l                                         |
|                                          | <b>Soil</b><br>2.89 mg/kg                                                           |
|                                          | <b>Marine water</b><br>0.68 mg/l                                                    |
| acetone                                  | <b>Fresh water</b><br>10.6 mg/l                                                     |
|                                          | <b>Marine water sediment</b><br>1.06 mg/l                                           |
|                                          | <b>Sediment</b><br>30.4 mg/kg                                                       |
|                                          | <b>Marine water sediment</b><br>3.04 mg/kg                                          |
|                                          | <b>Soil</b><br>29.5 mg/kg                                                           |
|                                          | <b>Sewage Treatment Plant</b><br>100 mg/l                                           |
| Reaction mass of ethylbenzene and xylene | <b>Fresh water</b><br>0.327 mg/l                                                    |
|                                          | <b>Marine water</b>                                                                 |

## SECTION 8: Exposure controls/personal protection

0.327 mg/l

### **Sewage Treatment Plant**

6.58 mg/l

### **Fresh water sediment**

12.46 mg/kg dwt

### **Marine water sediment**

12.46 mg/kg dwt

### **Soil**

2.31 mg/kg

## 8.2 Exposure controls

**Appropriate engineering controls** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Use safety eyewear designed to protect against splash of liquids.

### Skin protection

#### Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

**Gloves** : Duration / breakthrough time: <1 hour,  
Glove material: NBR, nitrile rubber, material thickness as splash protection: at least 0.2 mm, (EN374)  
Glove material: NBR, nitrile rubber, material thickness for short-term contact: at least 0.5 mm, (EN374)

The recommendation for the type or types of glove to use when handling this product is based on information from the following source:

Expert judgment

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Body protection** : Personnel should wear antistatic clothing made of natural fibers or of high-temperature-resistant synthetic fibers.

## SECTION 8: Exposure controls/personal protection

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.

Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

**Environmental exposure controls** : Do not allow to enter drains or watercourses.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

**Physical state** : Liquid.

**Color** : Clear.

**Odor** : Not available.

**Odor threshold** : Not available.

**Melting point/freezing point** : Technically not possible to measure

**Boiling point or initial boiling point and boiling range** : Not applicable.

**Flammability** : Not available.

**Lower and upper explosion limit** : Lower: 1.1%  
Upper: 26.2%

**Lower and upper explosive (flammable) limits** : Not available.

**Flash point** : Closed cup: -41°C

**Auto-ignition temperature** : 350°C

**Decomposition temperature** : Not applicable.

**pH** : Not applicable.

**Justification** : Not available.

**Viscosity** : Dynamic (room temperature): Not available.  
Kinematic (room temperature): Not available.  
Kinematic (40°C): Not available.

**Vapor pressure** : 209.1 kPa (1568.7 mm Hg)

**Density** : 0.772 g/cm<sup>3</sup>

**Weight volatiles** : 98.5 % (w/w)

**VOC content** : 98.5 % (w/w) (2010/75/EU)

### 9.2 Other information

#### 9.2.1 Information with regard to physical hazard classes

**Heat of combustion** : 35.02 kJ/g

#### Aerosol product

## SECTION 9: Physical and chemical properties

**Type of aerosol** : Spray

Further information Not available.

### 9.2.2 Other safety characteristics

**Miscible with water** : Yes.

Further information Not available.

*room temperature (=20°C)*

## SECTION 10: Stability and reactivity

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : Stable under recommended storage and handling conditions (see Section 7).

**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.

**10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

**10.6 Hazardous decomposition products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains hydrogen tetrakis[2,2-bis[(allyloxy)methyl]butan-1-olato-O1]bis(ditridecyl phosphito -O")titanate(2-). May produce an allergic reaction.

### Acute toxicity

| Product/ingredient name | Result |
|-------------------------|--------|
|-------------------------|--------|

**SECTION 11: Toxicological information**

toluene

**Rat - Dermal - TDLo**

26.4 mg/kg

Toxic effects: Skin After systemic exposure - Dermatitis, irritative Metabolism (intermediary) - Effect on inflammation or mediation of inflammation

**Rat - Oral - LD50**

5001 mg/kg

**Rat - Dermal - LD50**

5001 mg/kg

**Rat - Inhalation - LC50 Vapor**49 g/m<sup>3</sup> [4 hours]

dimethyl ether

**Rat - Oral - LD50**

&gt;99999 mg/kg

**Rat - Dermal - LD50**

&gt;99999 mg/kg

**Rat - Inhalation - LC50 Vapor**309 g/m<sup>3</sup> [4 hours]**Rat - Inhalation - LC50 Gas.**

164000 ppm [4 hours]

Toxic effects: Behavioral - Ataxia Behavioral - Coma

acetone

**Rat - Oral - LD50**

5800 mg/kg

Toxic effects: Behavioral - Altered sleep time (including change in righting reflex) Behavioral - Tremor

**Rabbit - Dermal - LD50**

2001 mg/kg

**Rat - Inhalation - LC50 Vapor**

21 mg/l [4 hours]

Reaction mass of ethylbenzene and xylene

**Rat - Oral - LD50**

3523 to 4000 mg/kg

**Rabbit - Dermal - LD50**

121236 mg/kg

**Rat - Inhalation - LC50 Vapor**

6350 to 6700 ppm [4 hours]

hydrogen tetrakis[2,2-bis[(allyloxy)methyl]  
butan-1-olato-O1]bis(ditridecyl phosphito -O")  
titanate(2-)

**Rat - Male, Female - Oral - LD50**

4600 mg/kg

OECD [Acute Oral Toxicity]

**Conclusion/Summary [Product]** : Not available.

**Acute toxicity estimates**

## SECTION 11: Toxicological information

| Product/ingredient name                                                                               | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapors) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|-------------------------------------------------------------------------------------------------------|--------------|----------------|--------------------------|----------------------------|-------------------------------------|
| mixture                                                                                               | N/A          | 43188.1        | N/A                      | 431.9                      | N/A                                 |
| toluene                                                                                               | 5001         | 5001           | N/A                      | 49                         | N/A                                 |
| dimethyl ether                                                                                        | N/A          | N/A            | 164000                   | 309                        | N/A                                 |
| acetone                                                                                               | 5800         | 2001           | N/A                      | 21                         | N/A                                 |
| Reaction mass of ethylbenzene and xylene                                                              | N/A          | 1100           | N/A                      | 11                         | N/A                                 |
| hydrogen tetrakis[2,2-bis[(allyloxy)methyl]butan-1-olato-O1]bis(ditridecyl phosphito -O")titanate(2-) | 4600         | N/A            | N/A                      | N/A                        | N/A                                 |

### Skin corrosion/irritation

#### Product/ingredient name

toluene

#### Result

##### **Pig - Skin - Mild irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 250 uL

##### **Rabbit - Skin - Mild irritant**

Amount/concentration applied: 435 mg

acetone

##### **Rabbit - Skin - Mild irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

##### **Rabbit - Skin - Mild irritant**

Amount/concentration applied: 395 mg

hydrogen tetrakis[2,2-bis[(allyloxy)methyl]  
butan-1-olato-O1]bis(ditridecyl phosphito -O")  
titanate(2-)

##### **Rabbit - Skin - Erythema/Eschar**

Duration of treatment/exposure: 4 hours

Observation period: 3 days

Irritation score: 2.7

**Conclusion/Summary [Product]** : Not available.

### Serious eye damage/eye irritation

#### Product/ingredient name

toluene

#### Result

##### **Rabbit - Eyes - Severe irritant**

Amount/concentration applied: 0.1 MI

acetone

##### **Human - Eyes - Mild irritant**

Amount/concentration applied: 186300 ppm

##### **Rabbit - Eyes - Mild irritant**

Amount/concentration applied: 10 uL

##### **Rabbit - Eyes - Moderate irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 20 mg

##### **Rabbit - Eyes - Severe irritant**

Amount/concentration applied: 20 mg

## SECTION 11: Toxicological information

**Conclusion/Summary [Product]** : Not available.

### Respiratory corrosion/irritation

Not available.

**Conclusion/Summary [Product]** : Not available.

### Respiratory or skin sensitization

#### **Product/ingredient name**

hydrogen tetrakis[2,2-bis[(allyloxy)methyl]  
butan-1-olato-O1]bis(ditridecyl phosphito -O")  
titanate(2-)

#### **Result**

##### **Mouse - skin**

Result: Sensitizing

#### **Skin**

**Conclusion/Summary [Product]** : Not available.

#### **Respiratory**

**Conclusion/Summary [Product]** : Not available.

### Germ cell mutagenicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Carcinogenicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Reproductive toxicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Specific target organ toxicity (single exposure)

#### **Product/ingredient name**

toluene  
acetone  
Reaction mass of ethylbenzene and xylene

#### **Result**

STOT SE 3, H336 (Narcotic effects)  
STOT SE 3, H336 (Narcotic effects)  
STOT SE 3, H335 (Respiratory tract irritation)

### Specific target organ toxicity (repeated exposure)

#### **Product/ingredient name**

toluene  
Reaction mass of ethylbenzene and xylene

#### **Result**

STOT RE 2, H373  
STOT RE 2, H373

### Aspiration hazard

## SECTION 11: Toxicological information

| Product/ingredient name                  | Result                         |
|------------------------------------------|--------------------------------|
| toluene                                  | ASPIRATION HAZARD - Category 1 |
| Reaction mass of ethylbenzene and xylene | ASPIRATION HAZARD - Category 1 |

### Information on the likely routes of exposure

Not available.

### Potential acute health effects

|                     |                                                                                         |
|---------------------|-----------------------------------------------------------------------------------------|
| <b>Eye contact</b>  | : Causes serious eye irritation.                                                        |
| <b>Inhalation</b>   | : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. |
| <b>Skin contact</b> | : Causes skin irritation.                                                               |
| <b>Ingestion</b>    | : Can cause central nervous system (CNS) depression.                                    |

### Symptoms related to the physical, chemical and toxicological characteristics

|                     |                                                                                                                                                                                                                                                                         |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Eye contact</b>  | : Adverse symptoms may include the following:<br>pain or irritation<br>watering<br>redness                                                                                                                                                                              |
| <b>Inhalation</b>   | : Adverse symptoms may include the following:<br>respiratory tract irritation<br>coughing<br>nausea or vomiting<br>headache<br>drowsiness/fatigue<br>dizziness/vertigo<br>unconsciousness<br>reduced fetal weight<br>increase in fetal deaths<br>skeletal malformations |
| <b>Skin contact</b> | : Adverse symptoms may include the following:<br>irritation<br>redness<br>reduced fetal weight<br>increase in fetal deaths<br>skeletal malformations                                                                                                                    |
| <b>Ingestion</b>    | : Adverse symptoms may include the following:<br>reduced fetal weight<br>increase in fetal deaths<br>skeletal malformations                                                                                                                                             |

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

|                                    |                  |
|------------------------------------|------------------|
| <b>Potential immediate effects</b> | : Not available. |
| <b>Potential delayed effects</b>   | : Not available. |

#### Long term exposure

|                                    |                  |
|------------------------------------|------------------|
| <b>Potential immediate effects</b> | : Not available. |
| <b>Potential delayed effects</b>   | : Not available. |

### Potential chronic health effects

Not available.

**Conclusion/Summary [Product]** : Not available.

**General** : May cause damage to organs through prolonged or repeated exposure.



## SECTION 11: Toxicological information

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : No known significant effects or critical hazards.

**Reproductive toxicity** : Suspected of damaging the unborn child.

### 11.2 Information on other hazards

#### 11.2.1 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]** : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

#### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

There are no data available on the mixture itself.

Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

#### Product/ingredient name

toluene

#### Result

##### Acute - LC50 - Fresh water

Fish - Coho salmon, silver salmon - *Oncorhynchus kisutch* - Fry

Weight: 1 g

5500 µg/l [96 hours]

Effect: Mortality

##### Acute - EC50 - Fresh water

Daphnia - Water flea - *Daphnia magna* - Juvenile (Fledgling, Hatchling, Weanling)

6000 µg/l [48 hours]

Effect: Intoxication

##### Chronic - NOEC - Fresh water

Daphnia - Water flea - *Daphnia magna*

Age: ≤24 hours

1 mg/l [21 days]

Effect: Mortality

##### Acute - EC50 - Fresh water

Algae - Green algae - *Raphidocelis subcapitata*

12.5 mg/l [72 hours]

Effect: Growth

acetone

##### Acute - LC50 - Fresh water

Daphnia - Water flea - *Daphnia magna*

10 mg/l [48 hours]

Effect: Mortality

##### Chronic - NOEC - Marine water

Algae - Green algae - *Ulva pertusa*

4.95 mg/l [96 hours]

Effect: Reproduction

SECTION 12: Ecological information

|                                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|--------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                                                                        | <p><b>Acute - EC50 - Marine water</b><br/>Algae - Green algae - <i>Ulva pertusa</i><br/>20.565 mg/l [96 hours]<br/><u>Effect</u>: Reproduction</p> <p><b>Chronic - NOEC - Fresh water</b><br/>Crustaceans - Daphnia - <i>Daphniidae</i><br/>0.016 ml/l [21 days]<br/><u>Effect</u>: Population</p> <p><b>Acute - LC50 - Fresh water</b><br/>Fish - Guppy - <i>Poecilia reticulata</i><br/><u>Age</u>: 4 to 12 months; <u>Size</u>: 2 to 10 cm; <u>Weight</u>: 0.5 to 14 g<br/>5600 ppm [96 hours]<br/><u>Effect</u>: Mortality</p> <p><b>Chronic - NOEC - Marine water</b><br/>Fish - Mummichog - <i>Fundulus heteroclitus</i><br/><u>Size</u>: 7.24 cm; <u>Weight</u>: 6.71 g<br/>0.1 mg/l [4 weeks]<br/><u>Effect</u>: Population</p> |
| Reaction mass of ethylbenzene and xylene                                                               | <p><b>Acute - LC50</b><br/>OECD 203<br/>Fish - Trout - <i>Oncorhynchus mykiss</i><br/>2.6 mg/l [96 hours]</p> <p><b>Acute - LC50</b><br/>OECD 202<br/>Daphnia - Daphnia - <i>Daphnia magna</i><br/>1 mg/l [24 hours]</p> <p><b>Acute - EC50</b><br/>OECD 201<br/>Algae - Algae - <i>Selenastrum capricornutum</i><br/>2.2 mg/l [73 hours]</p> <p><b>Chronic - NOEC</b><br/>OECD 301F<br/>Micro-organism - Activated sludge - <i>Activated sludge</i><br/>16 mg/l [28 days]</p>                                                                                                                                                                                                                                                          |
| hydrogen tetrakis[2,2-bis[(allyloxy)methyl]butan-1-olato-O1]bis(ditridecyl phosphito -O") titanate(2-) | <p><b>Acute - EC50 - Fresh water</b><br/>OECD [Daphnia sp. Acute Immobilization Test and Reproduction Test]<br/>Daphnia<br/>3.6 mg/l [48 hours]</p> <p><b>Acute - EC50</b><br/>OECD [Alga, Growth Inhibition Test]<br/>Algae<br/>&gt;100 mg/l [72 hours]</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

Conclusion/Summary [Product] : Not available.

## SECTION 12: Ecological information

### 12.2 Persistence and degradability

**Product/ingredient name**

acetone

**Result**

 OECD [Ready Biodegradability - CO<sub>2</sub> Evolution Test]  
 90.9% [28 days] - Readily

 hydrogen tetrakis[2,2-bis[(allyloxy)methyl]  
 butan-1-olato-O1]bis(ditridecyl phosphito -O")  
 titanate(2-)

 OECD [Ready Biodegradability - CO<sub>2</sub> Evolution Test]  
 40.3% [28 days] - Not readily

**Conclusion/Summary [Product]** : Not available.

**Ingredient name**

toluene

**Conclusion/Summary**

ECHA: toluene is readily biodegraded by both non-adapted and adapted sewage sludge inocula. Three of these studies were also used as part of a weight of evidence that toluene is readily biodegradable in the EU RAR for toluene (2003).

| Product/ingredient name                                                                               | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------------------------------------------------------------------------------------|-------------------|------------|------------------|
| toluene                                                                                               | -                 | -          | Readily          |
| acetone                                                                                               | -                 | -          | Readily          |
| hydrogen tetrakis[2,2-bis[(allyloxy)methyl]butan-1-olato-O1]bis(ditridecyl phosphito -O")titanate(2-) | -                 | -          | Not readily      |

### 12.3 Bioaccumulative potential

| Product/ingredient name                  | LogP <sub>ow</sub> | BCF | Potential |
|------------------------------------------|--------------------|-----|-----------|
| toluene                                  | 2.73               | 90  | Low       |
| dimethyl ether                           | 0.07               | -   | Low       |
| acetone                                  | -0.23              | -   | Low       |
| Reaction mass of ethylbenzene and xylene | 3.16               | -   | Low       |

### 12.4 Mobility in soil

**Soil/Water partition coefficient**

| Product/ingredient name | logK <sub>oc</sub> | K <sub>oc</sub> |
|-------------------------|--------------------|-----------------|
| toluene                 | 2.07               | 117.115         |
| dimethyl ether          | 0.44               | 2.76229         |
| acetone                 | 0.56               | 3.6548          |

**Results of PMT and vPvM assessment**

| Product/ingredient name                                                    | PMT | P  | M   | T   | vPvM | vP | vM  |
|----------------------------------------------------------------------------|-----|----|-----|-----|------|----|-----|
| toluene                                                                    | No  | No | Yes | Yes | No   | No | No  |
| dimethyl ether                                                             | No  | No | Yes | No  | No   | No | Yes |
| acetone                                                                    | No  | No | Yes | No  | No   | No | Yes |
| Reaction mass of ethylbenzene and xylene                                   | No  | No | No  | No  | No   | No | No  |
| hydrogen tetrakis[2,2-bis[(allyloxy)methyl]butan-1-olato-O1]bis(ditridecyl | No  | No | No  | No  | No   | No | No  |

## SECTION 12: Ecological information

phosphito -O")titanate(2-)

**Mobility** : Not available.**Conclusion/Summary** : The product does not meet the criteria to be considered as a PMT or vPvM.

### 12.5 Results of PBT and vPvB assessment

#### Regulation (EC) No. 1907/2006 [REACH]

| Product/ingredient name                                                                               | PBT | P  | B  | T   | vPvB | vP | vB |
|-------------------------------------------------------------------------------------------------------|-----|----|----|-----|------|----|----|
| toluene                                                                                               | No  | No | No | Yes | No   | No | No |
| dimethyl ether                                                                                        | No  | No | No | No  | No   | No | No |
| acetone                                                                                               | No  | No | No | No  | No   | No | No |
| Reaction mass of ethylbenzene and xylene                                                              | No  | No | No | No  | No   | No | No |
| hydrogen tetrakis[2,2-bis[(allyloxy)methyl]butan-1-olato-O1]bis(ditridecyl phosphito -O")titanate(2-) | No  | No | No | No  | No   | No | No |

#### Regulation (EC) No. 1272/2008 [CLP]

| Product/ingredient name                                                                               | PBT | P  | B  | T   | vPvB | vP | vB |
|-------------------------------------------------------------------------------------------------------|-----|----|----|-----|------|----|----|
| toluene                                                                                               | No  | No | No | Yes | No   | No | No |
| dimethyl ether                                                                                        | No  | No | No | No  | No   | No | No |
| acetone                                                                                               | No  | No | No | No  | No   | No | No |
| Reaction mass of ethylbenzene and xylene                                                              | No  | No | No | No  | No   | No | No |
| hydrogen tetrakis[2,2-bis[(allyloxy)methyl]butan-1-olato-O1]bis(ditridecyl phosphito -O")titanate(2-) | No  | No | No | No  | No   | No | No |

**Conclusion/Summary** : The product does not meet the criteria to be considered as a PBT or vPvB.

#### Regulation (EC) No. 1272/2008 [CLP]

### 12.6 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]** : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

## SECTION 13: Disposal considerations

- Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
- Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.
- Disposal considerations** : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

### Packaging

- Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
- Disposal considerations** : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

| Type of packaging | European waste catalogue (EWC) |                                                                          |
|-------------------|--------------------------------|--------------------------------------------------------------------------|
| CEPE Guidelines   | 15 01 10*                      | packaging containing residues of or contaminated by hazardous substances |

- Special precautions** : This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

## SECTION 14: Transport information

|                                        | ADR/RID                                                                                  | ADN                                                                                      | IMDG                                                                                        | IATA                                                                                         |
|----------------------------------------|------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|
| <b>14.1 UN number or ID number</b>     | UN1950                                                                                   | UN1950                                                                                   | UN1950                                                                                      | UN1950                                                                                       |
| <b>14.2 UN proper shipping name</b>    | AEROSOLS                                                                                 | AEROSOLS                                                                                 | AEROSOLS                                                                                    | Aerosols, flammable                                                                          |
| <b>14.3 Transport hazard class(es)</b> | 2<br> | 2<br> | 2.1<br> | 2.1<br> |
| <b>14.4 Packing group</b>              | -                                                                                        | -                                                                                        | -                                                                                           | -                                                                                            |
| <b>14.5 Environmental hazards</b>      | No.                                                                                      | Yes.                                                                                     | No.                                                                                         | No.                                                                                          |

### Additional information

**ADR/RID** : **Tunnel code** (D)

## SECTION 14: Transport information

**ADN** : The product is only regulated as an environmentally hazardous substance when transported in tank vessels.

**Marine pollutant** : Not available.

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Maritime transport in bulk according to IMO instruments** : Not applicable.

The actual shipping description for this product may vary based several factors including, but not limited to, the volume of material, size of the container, mode of transport and use of exemptions or exceptions found in the applicable regulations. The information provided in Section 14 is one possible shipping description for this product. Consult your shipping specialist or supplier for appropriate assignment information.

## SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

### EU Regulation (EC) No. 1907/2006 (REACH)

#### Annex XIV - List of substances subject to authorization

##### Annex XIV

None of the components are listed.

##### Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

### Other EU regulations

**Explosive precursors** : This product is regulated by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

#### Seveso Directive

This product may add to the calculation for determining whether a site is within the scope of the Seveso Directive on major accident hazards.

### National regulations

**Industrial use** : The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

**Flammable liquid class (SRVFS 2005:10)** : 1

## SECTION 15: Regulatory information

**15.2 Chemical Safety Assessment** : No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

**CEPE code** : 1

Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** :

- ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
- ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
- ATE = Acute Toxicity Estimate
- B = Bioaccumulative
- BCF = Bioconcentration Factor
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EUH statement = CLP-specific Hazard statement
- IATA = International Air Transport Association
- IMDG = International Maritime Dangerous Goods
- IMO = International Maritime Organization
- M = Mobile
- N/A = Not available
- P = Persistent
- PBT = Persistent, Bioaccumulative and Toxic
- PMT = Persistent, Mobile and Toxic
- PNEC = Predicted No Effect Concentration
- RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
- RRN = REACH Registration Number
- SGG = Segregation Group
- T = Toxic
- vB = Very Bioaccumulative
- vM = Very Mobile
- vP = Very Persistent
- vPvB = Very Persistent and Very Bioaccumulative
- vPvM = Very Persistent and Very Mobile

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification          | Justification         |
|-------------------------|-----------------------|
| Aerosol 1, H222, H229   | On basis of test data |
| Skin Irrit. 2, H315     | Calculation method    |
| Eye Irrit. 2, H319      | Calculation method    |
| Repr. 2, H361d          | Calculation method    |
| STOT SE 3, H336         | Calculation method    |
| STOT RE 2, H373         | Calculation method    |
| Aquatic Chronic 3, H412 | Calculation method    |

### Full text of abbreviated H statements

## SECTION 16: Other information

|                    |                                                                                                      |
|--------------------|------------------------------------------------------------------------------------------------------|
| H220<br>H222, H229 | Extremely flammable gas.<br>Extremely flammable aerosol. Pressurized container: may burst if heated. |
| H225<br>H226       | Highly flammable liquid and vapor.<br>Flammable liquid and vapor.                                    |
| H280               | Contains gas under pressure; may explode if heated.                                                  |
| H304               | May be fatal if swallowed and enters airways.                                                        |
| H312               | Harmful in contact with skin.                                                                        |
| H315               | Causes skin irritation.                                                                              |
| H317               | May cause an allergic skin reaction.                                                                 |
| H319               | Causes serious eye irritation.                                                                       |
| H332               | Harmful if inhaled.                                                                                  |
| H335               | May cause respiratory irritation.                                                                    |
| H336               | May cause drowsiness or dizziness.                                                                   |
| H361d              | Suspected of damaging the unborn child.                                                              |
| H373               | May cause damage to organs through prolonged or repeated exposure.                                   |
| H411               | Toxic to aquatic life with long lasting effects.                                                     |
| H412               | Harmful to aquatic life with long lasting effects.                                                   |
| EUH066             | Repeated exposure may cause skin dryness or cracking.                                                |

### Full text of classifications [CLP/GHS]

|                                                                                                                                                                                                                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Acute Tox. 4<br>Aerosol 1<br>Aquatic Chronic 2<br>Aquatic Chronic 3<br>Asp. Tox. 1<br>Eye Irrit. 2<br>Flam. Gas 1A<br>Flam. Liq. 2<br>Flam. Liq. 3<br>Press. Gas (Comp.)<br>Repr. 2<br>Skin Irrit. 2<br>Skin Sens. 1<br>STOT RE 2<br><br>STOT SE 3 | ACUTE TOXICITY - Category 4<br>AEROSOLS - Category 1<br>AQUATIC HAZARD (LONG-TERM) - Category 2<br>AQUATIC HAZARD (LONG-TERM) - Category 3<br>ASPIRATION HAZARD - Category 1<br>SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2<br>FLAMMABLE GASES - Category 1A<br>FLAMMABLE LIQUIDS - Category 2<br>FLAMMABLE LIQUIDS - Category 3<br>GASES UNDER PRESSURE - Compressed gas<br>TOXIC TO REPRODUCTION - Category 2<br>SKIN CORROSION/IRRITATION - Category 2<br>SKIN SENSITIZATION - Category 1<br>SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2<br>SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3 |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

**Date of issue/ Date of revision** : 13 May 2025

**Version** : 1.02

**Date of previous issue** : 13 May 2025

### Notice to reader

**This product is intended for industrial use only.**

**Safety Data Sheet (SDS) content is believed to be accurate as of its issue date, but is subject to change as new information is received by Axalta Coatings Systems, LLC or any of its subsidiaries or affiliates (Axalta). This SDS may incorporate information that has been provided to Axalta by its suppliers. Users should ensure that they are referring to the most current version of the SDS. Users are responsible for following the precautions identified in this SDS. It is the users' responsibility to comply with all laws and regulations applicable to the safe handling, use, and disposal of the product.**



## **SECTION 16: Other information**

Users of Axalta products should read all relevant product information prior to use, and make their own determination as to the suitability of the products for their intended use. Except as otherwise required by applicable law, AXALTA MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The information on this SDS relates only to the specific product identified in Section 1, Identification, and does not relate to its possible use in combination with any other material or in any specific process. If this product is to be used in combination with other products, Axalta encourages you to read and understand the SDS for all products prior to use.

© 2022 Axalta Coating Systems, LLC and all affiliates. All rights reserved. Copies may be made only for those using Axalta Coating Systems products.