

# SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product identifier** : UP2838  
**Product name** : 2K SLOW HARDENER  
**Product type** : Liquid.  
**Other means of identification** : 1250022891; 1250022892  
**Date of issue/ Date of revision** : 19 June 2025  
**Version** : 1.01  
**Date of previous issue** : 19 June 2025

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** : Coating component.  
**Uses advised against** : Not for sale to or use by consumers.

### 1.3 Details of the supplier of the safety data sheet

U-POL Limited  
Denington Road  
Wellingborough, Northamptonshire, NN8 2QH  
+44 (0) 1933 230310  
technicalsupport@u-pol.com

**e-mail address of person responsible for this SDS** : sds-competence@axalta.com

U-POL Netherlands  
B.V. Hoorgoorddreef 15  
Amsterdam, Netherlands 1101BA  
+31 20 240 2216  
technicalsupport@u-pol.com

### 1.4 Emergency telephone number

#### Supplier

**Telephone number** : +(44)-870-8200418

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to UK CLP/GHS

Flam. Liq. 3, H226  
Acute Tox. 4, H332  
Skin Sens. 1, H317  
STOT SE 3, H335  
STOT SE 3, H336  
Aquatic Chronic 2, H411

**SECTION 2: Hazards identification**

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

**2.2 Label elements****Hazard pictograms**

:

**Signal word**

: Warning

**Contains**: Hexamethylene diisocyanate, oligomers  
Hydrocarbons, C9, aromatics  
P-TOLUENESULFONYL ISOCYANATE**Hazard statements**: H226 - Flammable liquid and vapour.  
H317 - May cause an allergic skin reaction.  
H332 - Harmful if inhaled.  
H335 - May cause respiratory irritation.  
H336 - May cause drowsiness or dizziness.  
H411 - Toxic to aquatic life with long lasting effects.**Precautionary statements****Prevention**: P280 - Wear protective gloves.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P273 - Avoid release to the environment.  
P261 - Avoid breathing vapour.**Response**: P391 - Collect spillage.  
P302 + P352 - IF ON SKIN: Wash with plenty of water.**Storage**

: Not applicable.

**Disposal**

: Not applicable.

**Supplemental label elements**: EUH066 - Repeated exposure may cause skin dryness or cracking.  
EUH204 - Contains isocyanates. May produce an allergic reaction.**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles**

: Not applicable.

**2.3 Other hazards****Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII**

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**Other hazards which do not result in classification**

: None known.

**SECTION 3: Composition/information on ingredients****3.2 Mixtures**

: Mixture

**SECTION 3: Composition/information on ingredients**

| Product/ingredient name               | Identifiers                                                                           | %         | Classification                                                                                                                                                     | Type    |
|---------------------------------------|---------------------------------------------------------------------------------------|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| Hexamethylene diisocyanate, oligomers | REACH #:<br>01-2119485796-17<br>EC: 931-274-8<br>CAS: 28182-81-2                      | ≥25 - ≤48 | Acute Tox. 4, H332<br>Skin Sens. 1, H317<br>STOT SE 3, H335                                                                                                        | [1] [2] |
| Hydrocarbons, C9, aromatics           | REACH #:<br>01-2119455851-35<br>EC: 918-668-5                                         | ≥25 - ≤50 | Flam. Liq. 3, H226<br>STOT SE 3, H335<br>STOT SE 3, H336<br>Asp. Tox. 1, H304<br>Aquatic Chronic 2, H411<br>EUH066                                                 | [1]     |
| ethyl 3-ethoxypropionate              | REACH #:<br>01-2119463267-34<br>EC: 212-112-9<br>CAS: 763-69-9                        | ≥10 - ≤25 | Flam. Liq. 3, H226<br>EUH066                                                                                                                                       | [1]     |
| 2-butoxyethyl acetate                 | REACH #:<br>01-2119475112-47<br>EC: 203-933-3<br>CAS: 112-07-2<br>Index: 607-038-00-2 | ≤6.5      | Acute Tox. 4, H302<br>Acute Tox. 4, H312<br>Acute Tox. 4, H332                                                                                                     | [1] [2] |
| P-TOLUENESULFONYL ISOCYANATE          | REACH #:<br>01-2119980050-47<br>EC: 223-810-8<br>CAS: 4083-64-1                       | ≤0.2      | Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>Resp. Sens. 1, H334<br>STOT SE 3, H335<br><b>See Section 16 for the full text of the H statements declared above.</b> | [1]     |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a physical, health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

**SECTION 4: First aid measures****4.1 Description of first aid measures**

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

**SECTION 4: First aid measures**

- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

**4.2 Most important symptoms and effects, both acute and delayed****Over-exposure signs/symptoms**

- Eye contact** : No specific data.
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking
- Ingestion** : No specific data.

**4.3 Indication of any immediate medical attention and special treatment needed**

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

- Suitable extinguishing media** : Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray or mist.
- Unsuitable extinguishing media** : Do not use water jet.

**5.2 Special hazards arising from the substance or mixture**

- Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
- Hazardous combustion products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen, hydrogen cyanide, monomeric isocyanates.

**5.3 Advice for firefighters**

- Special protective actions for fire-fighters** : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

## SECTION 5: Firefighting measures

**Special protective equipment for fire-fighters** : Appropriate breathing apparatus may be required.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**6.2 Environmental precautions** : Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

### 6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Place in a suitable container. The contaminated area should be cleaned immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises (by volume): water (45 parts), ethanol or isopropyl alcohol (50 parts) and concentrated (d: 0,880) ammonia solution (5 parts). A non-flammable alternative is sodium carbonate (5 parts) and water (95 parts). Add the same decontaminant to the remnants and let stand for several days until no further reaction in an unsealed container. Once this stage is reached, close container and dispose of according to local regulations (see section 13).

**6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**Persons with a history of asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used.**

**Examination of lung function should be carried out on a regular basis on persons spraying this mixture.**

### 7.1 Precautions for safe handling

Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits.  
In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.  
Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type.  
Care should be taken when re-opening partly-used containers. Precautions should be taken to minimise exposure to atmospheric humidity or water. CO<sub>2</sub> will be formed, which, in closed containers, could result in pressurisation. Keep away from heat, sparks and flame. No sparking tools should be used.  
Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.  
Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8).  
Never use pressure to empty. Container is not a pressure vessel.  
Always keep in containers made from the same material as the original one.  
Comply with the health and safety at work laws.  
Do not allow to enter drains or watercourses.

#### Information on fire and explosion protection

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

### 7.2 Conditions for safe storage, including any incompatibilities

2K SLOW HARDENER

SECTION 7: Handling and storage

Store in accordance with local regulations.  
**Notes on joint storage**  
Keep away from: oxidising agents, strong alkalis, strong acids.  
**Additional information on storage conditions**  
Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight.  
Keep container tightly closed.  
Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Seveso Directive - Reporting thresholds

Danger criteria

| Category  | Notification and MAPP threshold | Safety report threshold    |
|-----------|---------------------------------|----------------------------|
| P5c<br>E2 | 5000 tonnes<br>200 tonnes       | 50000 tonnes<br>500 tonnes |

7.3 Specific end use(s)

**Recommendations** : Not available.  
**Industrial sector specific solutions** : Not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

|                                       |                                                                                                                                                                                                         |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Hexamethylene diisocyanate, oligomers | <b>EH40/2005 WELs (United Kingdom (UK), 1/2020) [isocyanates, all, except methyl isocyanate]</b> Inhalation sensitiser.<br>STEL 15 minutes: 0.07 mg/m³ (as -NCO).<br>TWA 8 hours: 0.02 mg/m³ (as -NCO). |
| 2-butoxyethyl acetate                 | <b>EH40/2005 WELs (United Kingdom (UK), 1/2020)</b> Absorbed through skin.<br>TWA 8 hours: 20 ppm.<br>STEL 15 minutes: 50 ppm.<br>STEL 15 minutes: 332 mg/m³.<br>TWA 8 hours: 133 mg/m³.                |

Biological exposure indices

No exposure indices known.

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: British Standard BS EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) British Standard BS EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) British Standard BS EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

| Product/ingredient name               | Result                                                                                                                                                                            |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Hexamethylene diisocyanate, oligomers | <b>DNEL - Workers - Long term - Inhalation</b><br>0.5 mg/m³<br><u>Effects</u> : Local<br><br><b>DNEL - Workers - Short term - Inhalation</b><br>1 mg/m³<br><u>Effects</u> : Local |
| Hydrocarbons, C9, aromatics           | <b>DNEL - Workers - Long term - Inhalation</b><br>151 mg/m³                                                                                                                       |

2K SLOW HARDENER

SECTION 8: Exposure controls/personal protection

|                          |                                                                                                        |
|--------------------------|--------------------------------------------------------------------------------------------------------|
|                          | <u>Effects</u> : Systemic                                                                              |
|                          | <b>DNEL - Workers - Long term - Dermal</b><br>12.5 mg/kg bw/day<br><u>Effects</u> : Systemic           |
| ethyl 3-ethoxypropionate | <b>DNEL - Workers - Long term - Inhalation</b><br>100.6 ppm<br><u>Effects</u> : Systemic               |
|                          | <b>DNEL - General population - Long term - Oral</b><br>1.2 mg/kg bw/day<br><u>Effects</u> : Systemic   |
|                          | <b>DNEL - General population - Long term - Dermal</b><br>3.1 mg/kg bw/day<br><u>Effects</u> : Systemic |
|                          | <b>DNEL - Workers - Long term - Dermal</b><br>8.85 mg/kg bw/day<br><u>Effects</u> : Systemic           |
|                          | <b>DNEL - General population - Long term - Inhalation</b><br>72.6 mg/m³<br><u>Effects</u> : Systemic   |
|                          | <b>DNEL - Workers - Long term - Inhalation</b><br>610 mg/m³<br><u>Effects</u> : Systemic               |
| 2-butoxyethyl acetate    | <b>DNEL - Workers - Long term - Inhalation</b><br>20 ppm<br><u>Effects</u> : Systemic                  |
|                          | <b>DNEL - Workers - Long term - Dermal</b><br>102 mg/kg bw/day<br><u>Effects</u> : Systemic            |
|                          | <b>DNEL - Workers - Long term - Inhalation</b><br>133 mg/m³<br><u>Effects</u> : Systemic               |
|                          | <b>DNEL - General population - Long term - Oral</b><br>8.6 mg/kg bw/day<br><u>Effects</u> : Systemic   |
|                          | <b>DNEL - General population - Short term - Oral</b><br>36 mg/kg bw/day<br><u>Effects</u> : Systemic   |
|                          | <b>DNEL - General population - Short term - Dermal</b><br>72 mg/kg bw/day<br><u>Effects</u> : Systemic |
|                          | <b>DNEL - General population - Long term - Dermal</b><br>102 mg/kg bw/day<br><u>Effects</u> : Systemic |
|                          | <b>DNEL - Workers - Short term - Dermal</b><br>120 mg/kg bw/day<br><u>Effects</u> : Systemic           |
|                          | <b>DNEL - Workers - Long term - Dermal</b>                                                             |

2K SLOW HARDENER

SECTION 8: Exposure controls/personal protection

169 mg/kg bw/day  
Effects: Systemic  
  
**DNEL - Workers - Short term - Inhalation**  
333 mg/m³  
Effects: Local

**PNECs**

**Product/ingredient name**  
Hexamethylene diisocyanate, oligomers

**Result**  
**Marine water**  
12.7 µg/l

**Fresh water**  
1270 µg/l

**Sediment**  
266700 mg/kg

**Soil**  
53200 mg/kg

**Sewage Treatment Plant**  
38.28 mg/kg

ethyl 3-ethoxypropionate

**Marine water**  
0.00609 mg/l

**Fresh water**  
0.0609 mg/l

**Sediment**  
0.0419 mg/l

2-butoxyethyl acetate

**Fresh water**  
0.304 mg/l

**Marine water**  
0.0304 mg/l

**Fresh water sediment**  
2.03 mg/kg dwt

**Marine water sediment**  
0.203 mg/kg dwt

**Soil**  
0.415 mg/kg dwt

**Sewage Treatment Plant**  
90 mg/l

**8.2 Exposure controls**

Persons with a history of asthma, allergies, chronic or recurrent respiratory disease should not be exposed to any process in which this product is used.

Examination of lung function should be carried out on a regular basis on persons spraying this mixture.

## SECTION 8: Exposure controls/personal protection

**Appropriate engineering controls** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. Air-fed protective respiratory equipment must be worn by the spray operator, even when good ventilation is provided. In other operations, if local exhaust ventilation and good general extraction are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn. (See Occupational exposure controls.)

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Use safety eyewear designed to protect against splash of liquids.

### Skin protection

#### **Hand protection**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

**Gloves** : Duration / breakthrough time: <1 hour,  
Glove material: NBR, nitrile rubber, material thickness as splash protection: at least 0.2 mm, (EN374)  
Glove material: NBR, nitrile rubber Material thickness for short-term contact: at least 0.5 mm, (EN374)  
The recommendation for the type or types of glove to use when handling this product is based on information from the following source:  
Expert judgment  
The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Body protection** : Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : By spraying: air-fed respirator.  
By other operations than spraying, in well ventilated areas, air-fed respirators could be replaced by a combination charcoal filter and particulate filter mask.  
  
Under cool, dry conditions, it is possible for the isocyanate to remain unreacted in the paint film for up to 30 hours after application. If dry flatting is unavoidable, air-fed respiratory protective equipment should be used.

**Environmental exposure controls** : Do not allow to enter drains or watercourses.

**SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

**9.1 Information on basic physical and chemical properties****Appearance**

|                                                     |                                                                                                                                  |
|-----------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| <b>Physical state</b>                               | : Liquid.                                                                                                                        |
| <b>Colour</b>                                       | : Clear.                                                                                                                         |
| <b>Odour</b>                                        | : Not available.                                                                                                                 |
| <b>Odour threshold</b>                              | : Not available.                                                                                                                 |
| <b>Melting point/freezing point</b>                 | : Technically not possible to measure                                                                                            |
| <b>Initial boiling point and boiling range</b>      | : 140 to 203°C (284 to 397.4°F)                                                                                                  |
| <b>Flammability (solid, gas)</b>                    | : Not available.                                                                                                                 |
| <b>Upper/lower flammability or explosive limits</b> | : Lower: 0.5%<br>Upper: 9.8%<br>Not available.                                                                                   |
| <b>Flash point</b>                                  | : Closed cup: 49.1°C (120.4°F)                                                                                                   |
| <b>Auto-ignition temperature</b>                    | : 280°C (536°F)                                                                                                                  |
| <b>Decomposition temperature</b>                    | : Not applicable.                                                                                                                |
| <b>pH</b>                                           | : Not applicable.                                                                                                                |
| <b>Viscosity</b>                                    | : Dynamic (room temperature): Not available.<br>Kinematic (room temperature): Not available.<br>Kinematic (40°C): Not available. |

**Solubility(ies)** :

| Media      | Result            |
|------------|-------------------|
| cold water | Partially soluble |

|                                                |                           |
|------------------------------------------------|---------------------------|
| <b>Solubility in water</b>                     | : Not available.          |
| <b>Miscible with water</b>                     | : No.                     |
| <b>Partition coefficient: n-octanol/ water</b> | : Not applicable.         |
| <b>Vapour pressure</b>                         | : 0.27 kPa (2 mm Hg)      |
| <b>Relative density</b>                        | : Not available.          |
| <b>Density</b>                                 | : 1 g/cm <sup>3</sup>     |
| <b>Vapour density</b>                          | : Not available.          |
| <b>Explosive properties</b>                    | : Not available.          |
| <b>Oxidising properties</b>                    | : Not available.          |
| <b>Weight volatiles</b>                        | : 56 % (w/w)              |
| <b>VOC content</b>                             | : 56 % (w/w) (2010/75/EU) |

**9.2 Other information****9.2.1 Information with regard to physical hazard classes**

Further information Not available.

**9.2.2 Other safety characteristics**

**Miscible with water** : No.

Further information Not available.

**room temperature (=20°C)**

2K SLOW HARDENER

SECTION 10: Stability and reactivity

|                                         |                                                                                                                                                                    |
|-----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 10.1 Reactivity                         | : The product reacts slowly with water, resulting in the production of carbon dioxide.                                                                             |
| 10.2 Chemical stability                 | : Stable under recommended storage and handling conditions (see Section 7).                                                                                        |
| 10.3 Possibility of hazardous reactions | : In closed containers, pressure build-up could result in distortion, expansion and, in extreme cases, bursting of the container.                                  |
| 10.4 Conditions to avoid                | : In a fire, hazardous decomposition products may be produced.                                                                                                     |
| 10.5 Incompatible materials             | : Keep away from: oxidising agents, strong alkalis, strong acids, amines, alcohols, water. Uncontrolled exothermic reactions occur with amines and alcohols.       |
| 10.6 Hazardous decomposition products   | : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen, hydrogen cyanide, monomeric isocyanates. |

SECTION 11: Toxicological information

11.1 Information on toxicological effects

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                               |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <u>Acute toxicity</u>                 |                                                                                                                                                                                                                                                                                                                                                                                                               |
| Product/ingredient name               | Result                                                                                                                                                                                                                                                                                                                                                                                                        |
| Hexamethylene diisocyanate, oligomers | <b>Rat - Inhalation - LC50 Dusts and mists</b><br>18500 mg/m³ [1 hours]                                                                                                                                                                                                                                                                                                                                       |
| Hydrocarbons, C9, aromatics           | <b>Rat - Female - Oral - LD50</b><br>3492 mg/kg<br>OECD 401<br><br><b>Rabbit - Dermal - LD50</b><br>>3160 mg/kg<br>OECD 402                                                                                                                                                                                                                                                                                   |
| ethyl 3-ethoxypropionate              | <b>Rat - Oral - LD50</b><br>3200 mg/kg<br><u>Toxic effects:</u> Behavioral - Ataxia<br><br><b>Rat - Male - Dermal - LD50</b><br>4080 mg/kg                                                                                                                                                                                                                                                                    |
| 2-butoxyethyl acetate                 | <b>Rabbit - Dermal - LD50</b><br>1500 mg/kg<br><u>Toxic effects:</u> Kidney, Ureter, and Bladder - Hematuria Kidney, Ureter, and Bladder - Other changes in urine composition<br>Blood - Normocytic anemia<br><br><b>Rat - Male, Female - Oral - LD50</b><br>1880 mg/kg<br>OECD [Acute Oral Toxicity]<br><br><b>Rat - Inhalation - LC50 Vapour</b><br>7.82 mg/l [4 hours]<br>OECD [Acute Inhalation Toxicity] |
| Conclusion/Summary [Product]          | : Not available.                                                                                                                                                                                                                                                                                                                                                                                              |

SECTION 11: Toxicological information

Acute toxicity estimates

| Product/ingredient name               | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapours) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|---------------------------------------|--------------|----------------|--------------------------|-----------------------------|-------------------------------------|
| mixture                               | 31565.3      | 25185.1        | N/A                      | 22.1                        | 3.4                                 |
| Hexamethylene diisocyanate, oligomers | N/A          | N/A            | N/A                      | 11                          | 1.5                                 |
| Hydrocarbons, C9, aromatics           | 3492         | N/A            | N/A                      | N/A                         | N/A                                 |
| ethyl 3-ethoxypropionate              | 3200         | 4080           | N/A                      | N/A                         | N/A                                 |
| 2-butoxyethyl acetate                 | 1880         | 1500           | N/A                      | 11                          | N/A                                 |

Skin corrosion/irritation

Product/ingredient name  
ethyl 3-ethoxypropionate

Result  
Rabbit - Skin - Mild irritant  
Duration of treatment/exposure: 24 hours  
Amount/concentration applied: 500 mg

Conclusion/Summary [Product] : Not available.

Serious eye damage/eye irritation

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Product/ingredient name  
Hexamethylene diisocyanate, oligomers

Result  
Mouse - skin  
OECD [Skin Sensitization: Local Lymph Node Assay]  
Result: Sensitising

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Not available.

**SECTION 11: Toxicological information****Reproductive toxicity**

Not available.

**Conclusion/Summary [Product]** : Not available.**Specific target organ toxicity (single exposure)**

| Product/ingredient name               | Result                                         |
|---------------------------------------|------------------------------------------------|
| Hexamethylene diisocyanate, oligomers | STOT SE 3, H335 (Respiratory tract irritation) |
| Hydrocarbons, C9, aromatics           | STOT SE 3, H335 (Respiratory tract irritation) |
|                                       | STOT SE 3, H336 (Narcotic effects)             |
| P-TOLUENESULFONYL ISOCYANATE          | STOT SE 3, H335 (Respiratory tract irritation) |

**Specific target organ toxicity (repeated exposure)**

Not available.

**Aspiration hazard**

| Product/ingredient name     | Result                         |
|-----------------------------|--------------------------------|
| Hydrocarbons, C9, aromatics | ASPIRATION HAZARD - Category 1 |

**Information on likely routes of exposure**

Not available.

**Potential acute health effects**

|                     |                                                                                                                                               |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Eye contact</b>  | : No known significant effects or critical hazards.                                                                                           |
| <b>Inhalation</b>   | : Harmful if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation. |
| <b>Skin contact</b> | : Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction.                                          |
| <b>Ingestion</b>    | : Can cause central nervous system (CNS) depression.                                                                                          |

**Symptoms related to the physical, chemical and toxicological characteristics**

|                     |                                                                                                                                                                                           |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Eye contact</b>  | : No specific data.                                                                                                                                                                       |
| <b>Inhalation</b>   | : Adverse symptoms may include the following:<br>respiratory tract irritation<br>coughing<br>nausea or vomiting<br>headache<br>drowsiness/fatigue<br>dizziness/vertigo<br>unconsciousness |
| <b>Skin contact</b> | : Adverse symptoms may include the following:<br>irritation<br>redness<br>dryness<br>cracking                                                                                             |
| <b>Ingestion</b>    | : No specific data.                                                                                                                                                                       |

**Delayed and immediate effects as well as chronic effects from short and long-term exposure****Short term exposure****Potential immediate effects** : Not available.**Potential delayed effects** : Not available.**Long term exposure**

2K SLOW HARDENER

SECTION 11: Toxicological information

|                                  |                                                                                                                                                                                                             |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Potential immediate effects      | : Not available.                                                                                                                                                                                            |
| Potential delayed effects        | : Not available.                                                                                                                                                                                            |
| Potential chronic health effects |                                                                                                                                                                                                             |
| Not available.                   |                                                                                                                                                                                                             |
| Conclusion/Summary [Product]     | : Not available.                                                                                                                                                                                            |
| General                          | : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/ or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. |
| Carcinogenicity                  | : No known significant effects or critical hazards.                                                                                                                                                         |
| Mutagenicity                     | : No known significant effects or critical hazards.                                                                                                                                                         |
| Reproductive toxicity            | : No known significant effects or critical hazards.                                                                                                                                                         |

Other information

Not available.

SECTION 12: Ecological information

|                                       |                                                                                              |
|---------------------------------------|----------------------------------------------------------------------------------------------|
| 12.1 Toxicity                         |                                                                                              |
| Product/ingredient name               | Result                                                                                       |
| Hexamethylene diisocyanate, oligomers | Acute - LC50<br>Fish - <i>danio rerio</i><br>>100 mg/l [96 hours]                            |
|                                       | Acute - EC50<br>Daphnia - <i>Daphnia magna</i><br>>100 mg/l [48 hours]                       |
| Hydrocarbons, C9, aromatics           | Acute - LC50<br>OECD 203<br>Fish - Trout - <i>Oncorhynchus mykiss</i><br>9.2 mg/l [96 hours] |
| ethyl 3-ethoxypropionate              | Acute - LC50<br>OECD [Fish, Acute Toxicity Test]<br>Fish<br>45.3 to 55.3 mg/l [96 hours]     |
| 2-butoxyethyl acetate                 | Chronic - LC50<br>Fish - Trout<br>11 mg/l [96 hours]                                         |
| Conclusion/Summary [Product]          | : Not available.                                                                             |
| 12.2 Persistence and degradability    |                                                                                              |
| Product/ingredient name               | Result                                                                                       |
| Hexamethylene diisocyanate, oligomers | Aerobic<br>1% [28 days] - Not readily                                                        |
| ethyl 3-ethoxypropionate              | OECD [ Ready Biodegradability - CO2 Evolution Test]<br>80% [13 days] - Readily               |
| 2-butoxyethyl acetate                 | >60% [28 days] - Readily                                                                     |
| Conclusion/Summary [Product]          | : Not available.                                                                             |

**SECTION 12: Ecological information**

| Product/ingredient name               | Aquatic half-life | Photolysis | Biodegradability |
|---------------------------------------|-------------------|------------|------------------|
| Hexamethylene diisocyanate, oligomers | -                 | -          | Not readily      |
| ethyl 3-ethoxypropionate              | -                 | -          | Readily          |
| 2-butoxyethyl acetate                 | -                 | -          | Readily          |

**12.3 Bioaccumulative potential**

| Product/ingredient name               | LogP <sub>ow</sub> | BCF   | Potential |
|---------------------------------------|--------------------|-------|-----------|
| Hexamethylene diisocyanate, oligomers | 5.54               | 367.7 | Low       |
| ethyl 3-ethoxypropionate              | 1.47               | -     | Low       |
| 2-butoxyethyl acetate                 | 1.51               | -     | Low       |

**12.4 Mobility in soil**

**Soil/water partition coefficient** : Not available.

**Mobility** : Not available.

**12.5 Results of PBT and vPvB assessment**

| Product/ingredient name               | PBT | P   | B   | T  | vPvB | vP  | vB  |
|---------------------------------------|-----|-----|-----|----|------|-----|-----|
| Hexamethylene diisocyanate, oligomers | No  | N/A | No  | No | No   | N/A | No  |
| Hydrocarbons, C9, aromatics           | No  | N/A | N/A | No | N/A  | N/A | N/A |
| ethyl 3-ethoxypropionate              | No  | N/A | N/A | No | N/A  | N/A | N/A |
| 2-butoxyethyl acetate                 | No  | N/A | N/A | No | N/A  | N/A | N/A |
| P-TOLUENESULFONYL ISOCYANATE          | No  | N/A | N/A | No | N/A  | N/A | N/A |

**12.6 Other adverse effects** : No known significant effects or critical hazards.

**SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**13.1 Waste treatment methods****Product**

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.

**Packaging**

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

2K SLOW HARDENER

**SECTION 13: Disposal considerations**

| Type of packaging | Waste catalogue                                                                       |
|-------------------|---------------------------------------------------------------------------------------|
|                   | 15 01 10*<br>packaging containing residues of or contaminated by hazardous substances |

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

**SECTION 14: Transport information**

|                                        | ADR/RID                                                                                                                                                                  | ADN                                                                                                                                                                      | IMDG                                                                                                                                                                        | IATA                                                                                     |
|----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|
| <b>14.1 UN number</b>                  | UN1263                                                                                                                                                                   | UN1263                                                                                                                                                                   | UN1263                                                                                                                                                                      | UN1263                                                                                   |
| <b>14.2 UN proper shipping name</b>    | PAINT RELATED MATERIAL                                                                                                                                                   | PAINT RELATED MATERIAL                                                                                                                                                   | PAINT RELATED MATERIAL                                                                                                                                                      | PAINT RELATED MATERIAL                                                                   |
| <b>14.3 Transport hazard class(es)</b> | 3<br>  | 3<br>  | 3<br>  | 3<br> |
| <b>14.4 Packing group</b>              | III                                                                                                                                                                      | III                                                                                                                                                                      | III                                                                                                                                                                         | III                                                                                      |
| <b>14.5 Environmental hazards</b>      | Yes.                                                                                                                                                                     | Yes.                                                                                                                                                                     | Yes.                                                                                                                                                                        | Yes. The environmentally hazardous substance mark is not required.                       |

**Additional information**

**ADR/RID** : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.  
**Tunnel code** (D/E)

**ADN** : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.

**IMDG** : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

**IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to IMO instruments** : Not available.

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****UK (GB)/REACH****Annex XIV - List of substances subject to authorisation****Annex XIV**

None of the components are listed.

**Substances of very high concern**

2K SLOW HARDENER

**SECTION 15: Regulatory information**

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles**

Not applicable.

**Seveso Directive**

This product is controlled under the Seveso Directive.

**Danger criteria****Category**P5c  
E2**National regulations**

| Product/ingredient name | List name | Name on list | Classification | Notes |
|-------------------------|-----------|--------------|----------------|-------|
|                         |           |              |                |       |

**International regulations****Chemical Weapon Convention List Schedules I, II & III Chemicals**

Not listed.

**Montreal Protocol**

Not listed.

**Stockholm Convention on Persistent Organic Pollutants**

Not listed.

**15.2 Chemical safety assessment**

: This product contains substances for which Chemical Safety Assessments are still required.

**SECTION 16: Other information**

Indicates information that has changed from previously issued version.

**Abbreviations and acronyms**

: ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway  
 ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road  
 ATE = Acute Toxicity Estimate  
 GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments  
 DMEL = Derived Minimal Effect Level  
 DNEL = Derived No Effect Level  
 EUH statement = GB CLP-specific Hazard statement  
 IATA = International Air Transport Association  
 IMDG = International Maritime Dangerous Goods  
 IMO = International Maritime Organization  
 N/A = Not available  
 PBT = Persistent, Bioaccumulative and Toxic  
 PNEC = Predicted No Effect Concentration  
 RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
 RRN = REACH Registration Number  
 SGG = Segregation Group  
 vPvB = Very Persistent and Very Bioaccumulative

**Procedure used to derive the classification**

2K SLOW HARDENER

**SECTION 16: Other information**

| Classification                                                                                                                  | Justification                                                                                                                       |
|---------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Flam. Liq. 3, H226<br>Acute Tox. 4, H332<br>Skin Sens. 1, H317<br>STOT SE 3, H335<br>STOT SE 3, H336<br>Aquatic Chronic 2, H411 | On basis of test data<br>Calculation method<br>Calculation method<br>Calculation method<br>Calculation method<br>Calculation method |

**Full text of abbreviated H statements**

|        |                                                                            |
|--------|----------------------------------------------------------------------------|
| H226   | Flammable liquid and vapour.                                               |
| H302   | Harmful if swallowed.                                                      |
| H304   | May be fatal if swallowed and enters airways.                              |
| H312   | Harmful in contact with skin.                                              |
| H315   | Causes skin irritation.                                                    |
| H317   | May cause an allergic skin reaction.                                       |
| H319   | Causes serious eye irritation.                                             |
| H332   | Harmful if inhaled.                                                        |
| H334   | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| H335   | May cause respiratory irritation.                                          |
| H336   | May cause drowsiness or dizziness.                                         |
| H411   | Toxic to aquatic life with long lasting effects.                           |
| EUH066 | Repeated exposure may cause skin dryness or cracking.                      |

**Full text of classifications**

|                   |                                                               |
|-------------------|---------------------------------------------------------------|
| Acute Tox. 4      | ACUTE TOXICITY - Category 4                                   |
| Aquatic Chronic 2 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2               |
| Asp. Tox. 1       | ASPIRATION HAZARD - Category 1                                |
| Eye Irrit. 2      | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2                |
| Flam. Liq. 3      | FLAMMABLE LIQUIDS - Category 3                                |
| Resp. Sens. 1     | RESPIRATORY SENSITISATION - Category 1                        |
| Skin Irrit. 2     | SKIN CORROSION/IRRITATION - Category 2                        |
| Skin Sens. 1      | SKIN SENSITISATION - Category 1                               |
| STOT SE 3         | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3 |

**Date of issue/ Date of revision** : 6/19/2025

**Version** : 1.01

**Date of previous issue** : 6/19/2025

**Notice to reader**

This product is intended for industrial use only.

Safety Data Sheet (SDS) content is believed to be accurate as of its issue date, but is subject to change as new information is received by Axalta Coatings Systems, LLC or any of its subsidiaries or affiliates (Axalta). This SDS may incorporate information that has been provided to Axalta by its suppliers. Users should ensure that they are referring to the most current version of the SDS. Users are responsible for following the precautions identified in this SDS. It is the users' responsibility to comply with all laws and regulations applicable to the safe handling, use, and disposal of the product.

Users of Axalta products should read all relevant product information prior to use, and make their own determination as to the suitability of the products for their intended use. Except as otherwise required by applicable law, AXALTA MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The information on this SDS relates only to the specific product identified in Section 1, Identification, and does not relate to its possible use in combination with any other material or in any specific process. If this product is to be used in combination with other products, Axalta encourages you to read and understand the SDS for all products prior to use.

© 2022 Axalta Coating Systems, LLC and all affiliates. All rights reserved. Copies may be made only for those using Axalta Coating Systems products.

2K SLOW HARDENER

SECTION 16: Other information