

## SAFETY DATA SHEET

### Section 1. Identification

**Product identifier** : UP4844  
**Product name** : RAPTOR 1K PRO PRIMER GRAY AEROSOL  
  
**Date of issue** : 6/19/2025  
**Version** : 1  
**Relevant identified uses of the substance or mixture and uses advised against**  
**Identified uses** : Coating component.  
**Uses advised against** : Not for sale to or use by consumers.  
  
**Supplier's details** : U-POL US Inc.  
50 Applied Bank Blvd.  
Suite 300  
Glen Mills, Pennsylvania 19342  
T (610) 746 7081  
technicalsupport@u-pol.com  
  
**Product information** (855) 6-AXALTA  
  
**Emergency telephone number** : CHEMTREC: +44 (0) 870 8200418 (24 hrs)

### Section 2. Hazards identification

**OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).  
**Classification of the substance or mixture** : AEROSOLS - Category 1  
EYE IRRITATION - Category 2A  
CARCINOGENICITY - Category 2  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

#### GHS label elements

**Hazard pictograms**



**Signal word**

: Danger

**Hazard statements**

: H222, H229 - Extremely flammable aerosol. Pressurized container: may burst if heated.  
H319 - Causes serious eye irritation.  
H336 - May cause drowsiness or dizziness.  
H351 - Suspected of causing cancer.  
H370 - Causes damage to organs.

#### Precautionary statements

## Section 2. Hazards identification

|                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|-----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Prevention</b>                       | : P201 - Obtain special instructions before use.<br>P280 - Wear protective gloves, protective clothing and eye or face protection.<br>P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.<br>P211 - Do not spray on an open flame or other ignition source.<br>P260 - Do not breathe dust or mist.<br>P270 - Do not eat, drink or smoke when using this product.<br>P251 - Do not pierce or burn, even after use. |
| <b>Response</b>                         | : P308 + P311 - IF exposed or concerned: Call a POISON CENTER or doctor.<br>P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell.<br>P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.<br>P337 + P313 - If eye irritation persists: Get medical advice or attention.                                                                     |
| <b>Storage</b>                          | : P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.<br>P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 122 °F/50 °C.                                                                                                                                                                                                                                                                                      |
| <b>Disposal</b>                         | : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.                                                                                                                                                                                                                                                                                                                                          |
| <b>Hazards not otherwise classified</b> | : None known.                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

## Section 3. Composition/information on ingredients

|                              |                 |             |  |
|------------------------------|-----------------|-------------|--|
| <b>Substance/mixture</b>     | : Mixture       |             |  |
| butanone                     | CAS: 78-93-3    | ≥15 - ≤40   |  |
| methyl acetate               | CAS: 79-20-9    | ≥3 - ≤7     |  |
| titanium dioxide             | CAS: 13463-67-7 | ≥1 - ≤5     |  |
| cyclohexane                  | CAS: 110-82-7   | ≥1 - ≤5     |  |
| acetone                      | CAS: 67-64-1    | ≥0.5 - ≤1.5 |  |
| carbon black, non respirable | CAS: 1333-86-4  | ≥0.1 - ≤1   |  |
| ethylbenzene                 | CAS: 100-41-4   | ≥0.1 - ≤1   |  |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are required to be classified as hazardous to health or the environment under the reporting requirements for this section.**

**Occupational exposure limits, if available, are listed in Section 8.**

## Section 4. First aid measures

### Description of necessary first aid measures

|                    |                                                                                                                                                                                                                                                              |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Eye contact</b> | : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician. |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## Section 4. First aid measures

- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Causes damage to organs following a single exposure if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : Causes damage to organs following a single exposure in contact with skin.
- Ingestion** : Causes damage to organs following a single exposure if swallowed. Can cause central nervous system (CNS) depression.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness
- Skin contact** : No specific data.
- Ingestion** : No specific data.

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

## Section 4. First aid measures

- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

- Specific hazards arising from the chemical** : Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
metal oxide/oxides

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

## Section 6. Accidental release measures

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

## Section 7. Handling and storage

### Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.
- Storage code** : IB

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

butanone

#### **NIOSH REL (United States, 10/2020)**

TWA 10 hours: 200 ppm.  
TWA 10 hours: 590 mg/m<sup>3</sup>.  
STEL 15 minutes: 300 ppm.  
STEL 15 minutes: 885 mg/m<sup>3</sup>.

#### **CAL OSHA PEL (United States, 5/2018)**

STEL 15 minutes: 885 mg/m<sup>3</sup>.  
STEL 15 minutes: 300 ppm.  
TWA 8 hours: 590 mg/m<sup>3</sup>.  
TWA 8 hours: 200 ppm.

#### **OSHA PEL (United States, 5/2018)**

TWA 8 hours: 200 ppm.

Section 8. Exposure controls/personal protection

methyl acetate

TWA 8 hours: 590 mg/m³.  
**OSHA PEL 1989 (United States, 3/1989)**  
TWA 8 hours: 200 ppm.  
TWA 8 hours: 590 mg/m³.  
STEL 15 minutes: 300 ppm.  
STEL 15 minutes: 885 mg/m³.  
**ACGIH TLV (United States, 1/2024)**  
Absorbed through skin.  
TWA 8 hours: 75 ppm.  
STEL 15 minutes: 150 ppm.

titanium dioxide

**NIOSH REL (United States, 10/2020)**  
TWA 10 hours: 200 ppm.  
TWA 10 hours: 610 mg/m³.  
STEL 15 minutes: 250 ppm.  
STEL 15 minutes: 760 mg/m³.  
**CAL OSHA PEL (United States, 5/2018)**  
STEL 15 minutes: 760 mg/m³.  
STEL 15 minutes: 250 ppm.  
TWA 8 hours: 610 mg/m³.  
TWA 8 hours: 200 ppm.  
**OSHA PEL (United States, 5/2018)**  
TWA 8 hours: 200 ppm.  
TWA 8 hours: 610 mg/m³.  
**OSHA PEL 1989 (United States, 3/1989)**  
TWA 8 hours: 200 ppm.  
TWA 8 hours: 610 mg/m³.  
STEL 15 minutes: 250 ppm.  
STEL 15 minutes: 760 mg/m³.  
**ACGIH TLV (United States, 1/2024)**  
TWA 8 hours: 200 ppm.  
TWA 8 hours: 606 mg/m³.  
STEL 15 minutes: 250 ppm.  
STEL 15 minutes: 757 mg/m³.

cyclohexane

**NIOSH REL (United States, 10/2020) NIA.**  
**CAL OSHA PEL (United States, 5/2018)**  
TWA 8 hours: 5 mg/m³ (as Ti). Form: respirable fraction.  
TWA 8 hours: 10 mg/m³ (as Ti). Form: total dust.  
**OSHA PEL (United States, 5/2018)**  
TWA 8 hours: 15 mg/m³. Form: Total dust.  
**OSHA PEL 1989 (United States, 3/1989)**  
TWA 8 hours: 10 mg/m³. Form: Total dust.  
**ACGIH TLV (United States, 1/2024) A3.**  
TWA 8 hours: 2.5 mg/m³. Form: respirable fraction, finescale particles.  
**NIOSH REL (United States, 10/2020)**  
TWA 10 hours: 300 ppm.  
TWA 10 hours: 1050 mg/m³.  
**CAL OSHA PEL (United States, 5/2018)**  
TWA 8 hours: 1050 mg/m³.  
TWA 8 hours: 300 ppm.  
**OSHA PEL (United States, 5/2018)**  
TWA 8 hours: 300 ppm.

## Section 8. Exposure controls/personal protection

acetone

TWA 8 hours: 1050 mg/m<sup>3</sup>.  
**OSHA PEL 1989 (United States, 3/1989)**  
TWA 8 hours: 300 ppm.  
TWA 8 hours: 1050 mg/m<sup>3</sup>.  
**ACGIH TLV (United States, 1/2024)**  
TWA 8 hours: 100 ppm.  
**NIOSH REL (United States, 10/2020)**  
TWA 10 hours: 250 ppm.  
TWA 10 hours: 590 mg/m<sup>3</sup>.  
**CAL OSHA PEL (United States, 5/2018)**  
STEL 15 minutes: 1780 mg/m<sup>3</sup>.  
STEL 15 minutes: 750 ppm.  
C: 3000 ppm.  
TWA 8 hours: 1200 mg/m<sup>3</sup>.  
TWA 8 hours: 500 ppm.  
**OSHA PEL (United States, 5/2018)**  
TWA 8 hours: 1000 ppm.  
TWA 8 hours: 2400 mg/m<sup>3</sup>.  
**OSHA PEL 1989 (United States, 3/1989)**  
TWA 8 hours: 750 ppm.  
TWA 8 hours: 1800 mg/m<sup>3</sup>.  
STEL 15 minutes: 1000 ppm.  
STEL 15 minutes: 2400 mg/m<sup>3</sup>.  
**ACGIH TLV (United States, 1/2024) A4.**  
TWA 8 hours: 250 ppm.  
STEL 15 minutes: 500 ppm.

carbon black, non respirable

**NIOSH REL (United States, 10/2020) NIA.**  
TWA 10 hours: 3.5 mg/m<sup>3</sup>.  
TWA 10 hours: 0.1 mg/m<sup>3</sup> (as cyclohexane-extractable fraction).  
**CAL OSHA PEL (United States, 5/2018)**  
TWA 8 hours: 3.5 mg/m<sup>3</sup>.  
**OSHA PEL (United States, 5/2018)**  
TWA 8 hours: 3.5 mg/m<sup>3</sup>.  
**OSHA PEL 1989 (United States, 3/1989)**  
TWA 8 hours: 3.5 mg/m<sup>3</sup>.  
**ACGIH TLV (United States, 1/2024) A3.**  
TWA 8 hours: 3 mg/m<sup>3</sup>. Form: Inhalable fraction.

ethylbenzene

**NIOSH REL (United States, 10/2020)**  
TWA 10 hours: 100 ppm.  
TWA 10 hours: 435 mg/m<sup>3</sup>.  
STEL 15 minutes: 125 ppm.  
STEL 15 minutes: 545 mg/m<sup>3</sup>.  
**CAL OSHA PEL (United States, 5/2018)**  
STEL 15 minutes: 130 mg/m<sup>3</sup>.  
STEL 15 minutes: 30 ppm.  
TWA 8 hours: 22 mg/m<sup>3</sup>.  
TWA 8 hours: 5 ppm.  
**OSHA PEL (United States, 5/2018)**  
TWA 8 hours: 100 ppm.  
TWA 8 hours: 435 mg/m<sup>3</sup>.  
**OSHA PEL 1989 (United States, 3/1989)**  
TWA 8 hours: 100 ppm.  
TWA 8 hours: 435 mg/m<sup>3</sup>.

## Section 8. Exposure controls/personal protection

STEL 15 minutes: 125 ppm.

STEL 15 minutes: 545 mg/m<sup>3</sup>.

**ACGIH TLV (United States, 1/2024) A3.**

Ototoxicant.

TWA 8 hours: 20 ppm.

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

### Appearance

|                                              |                                                                                                                                          |
|----------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Physical state                               | : Liquid.                                                                                                                                |
| Color                                        | : Gray.                                                                                                                                  |
| Odor                                         | : Not available.                                                                                                                         |
| Odor threshold                               | : Not available.                                                                                                                         |
| pH                                           | : Not applicable.                                                                                                                        |
| Melting point                                | : Technically not possible to measure                                                                                                    |
| Boiling point                                | : Not applicable.                                                                                                                        |
| Flash point                                  | : Closed cup: -41°C (-41.8°F)                                                                                                            |
| Evaporation rate                             | : Not available.                                                                                                                         |
| Flammability (solid, gas)                    | : Not available.                                                                                                                         |
| Lower and upper explosive (flammable) limits | : Lower: 1%<br>Upper: 26.2%                                                                                                              |
| Vapor pressure                               | : 210.6 kPa (1579.3 mm Hg)                                                                                                               |
| Vapor density                                | : Not available.                                                                                                                         |
| Density                                      | : 0.824 g/cm <sup>3</sup>                                                                                                                |
| Partition coefficient: n-octanol/water       | : Not applicable.                                                                                                                        |
| Auto-ignition temperature                    | : 260°C (500°F)                                                                                                                          |
| Decomposition temperature                    | : Not applicable.                                                                                                                        |
| Viscosity                                    | : Dynamic (room temperature): Not available.<br>Kinematic (room temperature): Not available.<br>Kinematic (40°C (104°F)): Not available. |
| Flow time (ISO 2431)                         | : Not available.                                                                                                                         |
| Aerosol product                              |                                                                                                                                          |
| Type of aerosol                              | : Spray                                                                                                                                  |
| Heat of combustion                           | : 25.39 kJ/g                                                                                                                             |

## Section 10. Stability and reactivity

|                                    |                                                                                                        |
|------------------------------------|--------------------------------------------------------------------------------------------------------|
| Reactivity                         | : No specific test data related to reactivity available for this product or its ingredients.           |
| Chemical stability                 | : The product is stable.                                                                               |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur.                      |
| Conditions to avoid                | : Avoid all possible sources of ignition (spark or flame).                                             |
| Incompatible materials             | : No specific data.                                                                                    |
| Hazardous decomposition products   | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

| Product/ingredient name | Result |
|-------------------------|--------|
|-------------------------|--------|

Section 11. Toxicological information

|                              |                                                                                                                                                                                                                                        |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| butanone                     | <b>Rabbit - Dermal - LD50</b><br>6480 mg/kg<br><b>Rat - Oral - LD50</b><br>2737 mg/kg<br><b>Rat - Oral - LD50</b><br>>5 g/kg<br><b>Rabbit - Dermal - LD50</b><br>>5 g/kg                                                               |
| methyl acetate               | <b>Rat - Oral - LD50</b><br>6240 mg/kg<br><b>Toxic effects:</b> Behavioral - Somnolence (general depressed activity) Gastrointestinal - Changes in structure or function of salivary glands Gastrointestinal - Hypermotility, diarrhea |
| cyclohexane                  | <b>Rat - Oral - LD50</b><br>5800 mg/kg<br><b>Toxic effects:</b> Behavioral - Altered sleep time (including change in righting reflex) Behavioral - Tremor                                                                              |
| acetone                      | <b>Rabbit - Dermal - LD50</b><br>2001 mg/kg<br><b>Rat - Inhalation - LC50 Vapor</b><br>21 mg/l [4 hours]<br><b>Rat - Oral - LD50</b><br>>15400 mg/kg<br><b>Toxic effects:</b> Behavioral - Somnolence (general depressed activity)     |
| carbon black, non respirable | <b>Rat - Oral - LD50</b><br>3500 mg/kg<br><b>Toxic effects:</b> Liver - Other changes Kidney, Ureter, and Bladder - Other changes                                                                                                      |
| ethylbenzene                 | <b>Rabbit - Dermal - LD50</b><br>>5000 mg/kg                                                                                                                                                                                           |

Conclusion/Summary [Product] : Not available.

Skin corrosion/irritation

Product/ingredient name

|                |                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| butanone       | <b>Result</b><br><b>Rabbit - Skin - Mild irritant</b><br><u>Duration of treatment/exposure:</u> 24 hours<br><u>Amount/concentration applied:</u> 14 mg<br><b>Rabbit - Skin - Mild irritant</b><br><u>Duration of treatment/exposure:</u> 24 hours<br><u>Amount/concentration applied:</u> 402 mg<br><b>Rabbit - Skin - Moderate irritant</b><br><u>Duration of treatment/exposure:</u> 24 hours<br><u>Amount/concentration applied:</u> 500 mg |
| methyl acetate | <b>Rabbit - Skin - Mild irritant</b><br><u>Duration of treatment/exposure:</u> 24 hours<br><u>Amount/concentration applied:</u> 500 mg<br><b>Rabbit - Skin - Moderate irritant</b><br><u>Duration of treatment/exposure:</u> 24 hours<br><u>Amount/concentration applied:</u> 20 mg                                                                                                                                                            |
| acetone        | <b>Rabbit - Skin - Mild irritant</b><br><u>Duration of treatment/exposure:</u> 24 hours                                                                                                                                                                                                                                                                                                                                                        |

## Section 11. Toxicological information

ethylbenzene

Amount/concentration applied: 500 mg

**Rabbit - Skin - Mild irritant**

Amount/concentration applied: 395 mg

**Rabbit - Skin - Mild irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 15 mg

**Conclusion/Summary [Product]** : Not available.

### Serious eye damage/eye irritation

**Product/ingredient name**

methyl acetate

**Result**

**Rabbit - Eyes - Moderate irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 100 mg

**Rabbit - Eyes - Severe irritant**

Amount/concentration applied: 0.1 Ml

**Human - Eyes - Mild irritant**

Amount/concentration applied: 186300 ppm

**Rabbit - Eyes - Mild irritant**

Amount/concentration applied: 10 uL

**Rabbit - Eyes - Moderate irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 20 mg

**Rabbit - Eyes - Severe irritant**

Amount/concentration applied: 20 mg

**Conclusion/Summary [Product]** : Not available.

### Respiratory corrosion/irritation

Not available.

**Conclusion/Summary [Product]** : Not available.

### Respiratory or skin sensitization

Not available.

### **Skin**

**Conclusion/Summary [Product]** : Not available.

### **Respiratory**

**Conclusion/Summary [Product]** : Not available.

### Germ cell mutagenicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Carcinogenicity

Section 11. Toxicological information

Not available.

Conclusion/Summary [Product] : Not available.

Classification

| Product/ingredient name      | OSHA | IARC | NTP |
|------------------------------|------|------|-----|
| titanium dioxide             | -    | 2B   | -   |
| carbon black, non respirable | -    | 2B   | -   |
| ethylbenzene                 | -    | 2B   | -   |

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

| Product/ingredient name | Result                                                                              |
|-------------------------|-------------------------------------------------------------------------------------|
| butanone                | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)<br>(Narcotic effects) - Category 3 |
| methyl acetate          | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) -<br>Category 1                    |
| cyclohexane             | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)<br>(Narcotic effects) - Category 3 |
| acetone                 | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)<br>(Narcotic effects) - Category 3 |

Specific target organ toxicity (repeated exposure)

| Product/ingredient name | Result                                                             |
|-------------------------|--------------------------------------------------------------------|
| ethylbenzene            | SPECIFIC TARGET ORGAN TOXICITY (REPEATED<br>EXPOSURE) - Category 2 |

Aspiration hazard

| Product/ingredient name | Result                         |
|-------------------------|--------------------------------|
| cyclohexane             | ASPIRATION HAZARD - Category 1 |
| ethylbenzene            | ASPIRATION HAZARD - Category 1 |

Information on the likely routes of exposure

Not available.

Potential acute health effects

|              |                                                                                                                                                         |
|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| Eye contact  | : Causes serious eye irritation.                                                                                                                        |
| Inhalation   | : Causes damage to organs following a single exposure if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. |
| Skin contact | : Causes damage to organs following a single exposure in contact with skin.                                                                             |

## Section 11. Toxicological information

**Ingestion** : Causes damage to organs following a single exposure if swallowed. Can cause central nervous system (CNS) depression.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

**Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness

**Skin contact** : No specific data.

**Ingestion** : No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### **Short term exposure**

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### **Long term exposure**

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

### Potential chronic health effects

#### **Result**

Not available.

**Conclusion/Summary [Product]** : Not available.

**General** : No known significant effects or critical hazards.

**Carcinogenicity** : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

**Mutagenicity** : No known significant effects or critical hazards.

**Reproductive toxicity** : No known significant effects or critical hazards.

### Numerical measures of toxicity

#### **Acute toxicity estimates**

## Section 11. Toxicological information

| Product/ingredient name      | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapors) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|------------------------------|--------------|----------------|--------------------------|----------------------------|-------------------------------------|
| HIGH 5 G MIR DME (OALHI5VG1) | 8564.4       | 173246.8       | N/A                      | N/A                        | N/A                                 |
| butanone                     | 2737         | 6480           | N/A                      | N/A                        | N/A                                 |
| cyclohexane                  | 6240         | N/A            | N/A                      | N/A                        | N/A                                 |
| acetone                      | 5800         | 2001           | N/A                      | 21                         | N/A                                 |
| ethylbenzene                 | 3500         | N/A            | N/A                      | 11                         | N/A                                 |

## Section 12. Ecological information

There are no data available on the product itself. The product should not be allowed to enter drains or watercourses waterways.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

## Section 14. Transport information

|                            | DOT Classification                                                                         | TDG Classification                                                                         | Mexico Classification                                                                      | IMDG                                                                                         | IATA                                                                                         |
|----------------------------|--------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|
| UN number                  | UN1950                                                                                     | UN1950                                                                                     | UN1950                                                                                     | UN1950                                                                                       | UN1950                                                                                       |
| UN proper shipping name    | AEROSOLS                                                                                   | AEROSOLS                                                                                   | AEROSOLS                                                                                   | AEROSOLS                                                                                     | Aerosols, flammable                                                                          |
| Transport hazard class(es) | 2.1<br> | 2.1<br> | 2.1<br> | 2.1<br> | 2.1<br> |
| Packing group              | -                                                                                          | -                                                                                          | -                                                                                          | -                                                                                            | -                                                                                            |
| Environmental hazards      | No.                                                                                        | No.                                                                                        | No.                                                                                        | No.                                                                                          | No.                                                                                          |

### Additional information

**DOT Classification** : **Reportable quantity** 15645.5 lbs / 7103.1 kg [2277.2 gal / 8620.2 L]. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.

**TDG Classification** : Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.13-2.17 (Class 2).

## Section 14. Transport information

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to IMO instruments** : Not available.

The actual shipping description for this product may vary based several factors including, but not limited to, the volume of material, size of the container, mode of transport and use of exemptions or exceptions found in the applicable regulations. The information provided in Section 14 is one possible shipping description for this product. Consult your shipping specialist or supplier for appropriate assignment information.

## Section 15. Regulatory information

### TSCA 12(b) - Chemical export notification

Not applicable.

**Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)** : Listed

### SARA 304 RQ

**SARA 304 RQ** : Not applicable.

### SARA 311/312

**Classification** : AEROSOLS - Category 1  
EYE IRRITATION - Category 2A  
CARCINOGENICITY - Category 2  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

### SARA 313

|                                        | Product name | CAS number | %         |
|----------------------------------------|--------------|------------|-----------|
| <b>Form R - Reporting requirements</b> | cyclohexane  | 110-82-7   | ≥1 - ≤5   |
|                                        | ethylbenzene | 100-41-4   | ≥0.1 - ≤1 |
| <b>Supplier notification</b>           | cyclohexane  | 110-82-7   | ≥1 - ≤5   |
|                                        | ethylbenzene | 100-41-4   | ≥0.1 - ≤1 |

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

### Inventory list

**Canada** : At least one component is not listed.

**United States** : All components are listed or exempted.

## Section 16. Other information

### Hazardous Material Information System (U.S.A.)


|                  |   |   |
|------------------|---|---|
| Health           | * | 4 |
| Flammability     |   | 3 |
| Physical hazards |   | 0 |
|                  |   |   |

## Section 16. Other information

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

### National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

### History

Date of issue : 6/19/2025

Version : 1

Product stewardship and regulatory compliance.

### Key to abbreviations

: ATE = Acute Toxicity Estimate

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

▀ Indicates information that has changed from previously issued version.

### Notice to reader

This product is intended for industrial use only.

Safety Data Sheet (SDS) content is believed to be accurate as of its issue date, but is subject to change as new information is received by Axalta Coatings Systems, LLC or any of its subsidiaries or affiliates (Axalta). This SDS may incorporate information that has been provided to Axalta by its suppliers. Users should ensure that they are referring to the most current version of the SDS. Users are responsible for following the precautions identified in this SDS. It is the users' responsibility to comply with all laws and regulations applicable to the safe handling, use, and disposal of the product.

Users of Axalta products should read all relevant product information prior to use, and make their own determination as to the suitability of the products for their intended use. Except as otherwise required by applicable law, AXALTA MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The information on this SDS relates only to the specific product identified in Section 1, Identification, and does not relate to its possible use in combination with any other material or in any specific process. If this product is to be used in combination with other products, Axalta encourages you to read and understand the SDS for all products prior to use.

© 2022 Axalta Coating Systems, LLC and all affiliates. All rights reserved. Copies may be made only for those using Axalta Coating Systems products.